

Coaxial Shorts



DESCRIPTION

The shorts are used to provide measurement planes and known reflection phase and magnitude in 50 Ohm coaxial systems.

SPECIFICATIONS

Model	Frequency range, GHz	Length of a phase shifting section, mm	Connector type	Dimensions, mm	Weight, kg
2.260.205	0-18	0	N(m,f)	Ø 23x78	0.1
2.260.206	8-18	7.5	N(m,f)	Ø 23x80	0.1
2.260.206-01	4-8	12.5	N(m,f)	Ø 23x80	0.1
2.260.206-02	2-4	25	N(m,f)	Ø 23x80	0.1
2.260.207	0-18	0	3.5(f)	Ø 14x50	0,05
2.260.229	0-18	0	3.5(m)	Ø 8.6x36	0.05
2.260.193	2-18	4	3.5(m,f)	Ø 14x68	0.1
2.260.193-01	8-18	7.5	3.5(m,f)	Ø 14x68	0.1
2.260.193-02	4-8	12.5	3.5(m,f)	Ø 14x68	0.1
2.260.193-03	2-4	25	3.5(m,f)	Ø 14x68	0.1
468.548.007	0-50	0	2.4(m)	Ø 10x26	0.025
468.548.008	0-50	0	2.4(f)	Ø 10x26	0.025

Note: It is possible to manufacture terminations with III and IX type connectors (in accordance with ГOCT 13317-89) instead of N and 3.5 mm type connectors accordingly.