

Coaxial Sliding Terminations



DESCRIPTION

The slidings terminations are movable 50 Ohm, low reflection loads for precision measurements. Loads travel at least one-half a wavelength at the lowest specified frequency.

SPECIFICATIONS

Model	Frequency range, GHz	Coaxial airline VSWR	Termination element VSWR	Connector type	Dimensions, mm	Weight kg
2.260.181	2-18	1.01	1.1	N(m)	Ø 23x400	0.2
2.260.181-01	2-18	1.01	1.1	N(f)	Ø 23x400	0.2
2.260.203	2-18	1.01	1.2	N(m)	Ø 23x400	0.2
2.260.186	3-18	1.01	1.1	3.5(m)	Ø 16x280	0.15
2.260.186-01	3-18	1.01	1.2	3.5(f)	Ø 16x280	0.15
2.260.204	3-18	1.01	1.2	3.5(m)	Ø 16x280	0.15
468.548.003	4-18	1.01	1.1	2.4(m)	Ø 14x165	0.1
468.548.003-01	10-50	1.01	1.1	2.4(f)	Ø 14x105	0.1
468.548.003-02	10-50	1.01	1.1	2.4(m)	Ø 14x105	0.075
468.548.003-03	10-50	1.01	1.1	2.4(f)	Ø 14x105	0.075
468.548.005-02	17.44	1.01	1.2	2.4(m)	Ø 14x105	0.075
468.548.005-03	-37.5 -"-	1.01	1.2	2.4(f)	Ø 14x105	0.075

Note: It is possible to manufacture coaxial terminations with III and IX type connectors (in accordance with ГOCT 13317-89) instead of N and 3.5 mm type connectors accordingly.